



Ultra1Plus™ SAE 75W-90 Synthetic gear oil API GL-5

Product description

Ultra1Plus™ SAE 75W-90 Synthetic gear oil, API GL-5 is formulated with synthetic base oils and specialty performance additives to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions. Specialty anti-scuffing additives and friction modifiers provide advanced protection and lubricity in extreme pressure conditions.

Additionally, **Ultra1Plus™ SAE 75W-90 Synthetic gear oil, API GL-5** is designed for use in all seasons and exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5.

Product features & benefits

- Extended gear and bearing life due to minimal deposits.
- Longer seal life.
- Increased load-carrying capability.
- Contribution to reduced maintenance cost and longer equipment life.

Product codes

Presentation	SKU	UPC
1.05 QT / 1 Liter	UFS7590GL5L	810050654142
US Gallon (4 QT)	UFS7590GL5G	810050654135
5 Gallon Pail	UFS7590GL5P	810050654128
55 Gallon Drum	UFS7590GL5D	810050654111

Product features & benefits

API GL-5

Typical properties

SAE J306 Viscosity Grade	75W-90
Appearance	Yellow, transparent liquid
Viscosity @ 40°C, cSt, ASTM D445	113.2
Viscosity @ 100°C, cSt, ASTM D445	15.5
Viscosity index, ASTM D2270	145
Flash point, °C, ASTM D92	205
Pour point, °C, ASTM D97	-50



Revised: 01/07/2021