



FULL SYNTHETIC

| MID | CATEGORY | VISCOSITY | SPECIFICATION |
|-------|----------|-------------|---------------|
| UL703 | Gear Oil | SAE 75W-90 | API GL-5 |
| UL704 | Gear Oil | SAE 80W-140 | API GL-5 |
| UL705 | Gear Oil | SAE 75W-140 | API GL-5 |
| UL706 | Gear Oil | SAE 75W-90 | API GL-4 |
| UL717 | Gear Oil | ISO 220 | VG |

MINERAL-BASED

| MID | CATEGORY | VISCOSITY | SPECIFICATION |
|-------|----------|-------------|---------------|
| UL701 | Gear Oil | SAE 80W-90 | API GL-5 |
| UL702 | Gear Oil | SAE 85W-140 | API GL-5 |
| UL707 | Gear Oil | ISO 220 | EP |
| UL708 | Gear Oil | ISO 320 | EP |
| UL709 | Gear Oil | ISO 460 | EP |
| UL710 | Gear Oil | ISO 68 | EP |
| UL711 | Gear Oil | ISO 100 | EP |
| UL712 | Gear Oil | ISO 150 | EP |
| UL713 | Gear Oil | SAE 90 | API GL-5 |
| UL714 | Gear Oil | SAE 140 | API GL-5 |



QUART (0.95 L)



US GALLON (4 QT)



JUG (5QT)



TIGHT-HEAD (5 GALLON)



PAIL (5 GALLON)



DRUM (55 GALLON)



TOTE (265 GALLON)